



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

Address: COMMISSIONER FOR PATENTS

P.O. Box 1450

Alexandria, Virginia 22313-1450

www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/771,412	02/05/2004	Kazuma Aoki	118332	3848
25944 7590 12/10/2007 OLIFF & BERRIDGE, PLC P.O. BOX 320850 ALEXANDRIA, VA 22320-4850				
EXAMINER				
NAJEE-ULLAH, TARIQ S				
ART UNIT		PAPER NUMBER		
4121				
MAIL DATE		DELIVERY MODE		
12/10/2007		PAPER		

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

### Office Action Summary

**Application No.**

10/771,412

**Applicant(s)**

AOKI ET AL.

**Examiner**

Tariq S. Najee-ullah

**Art Unit**

4121

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --  
**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 05 February 2004.  
2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.  
3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-25 is/are pending in the application.  
4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.  
5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.  
6) ☒ Claim(s) 1-25 is/are rejected.  
7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.  
8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☒ The specification is objected to by the Examiner.  
10) ☒ The drawing(s) filed on 02/05/2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).  
11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).  
a) ☒ All b) ☐ Some \* c) ☐ None of:  
1. ☒ Certified copies of the priority documents have been received.  
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.  
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- 1) ☒ Notice of References Cited (PTO-892)  
2) ☐ Notice of Draftperson's Patent Drawing Review (PTO-948)  
3) ☒ Information Disclosure Statement(s) (PTO-85/86)  
Paper No(s)/Mail Date 06/21/04, 06/08/07, 07/27/07  
4) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date \_\_\_\_\_  
5) ☐ Notice of Informal Patent Application  
6) ☐ Other: \_\_\_\_\_

Art Unit: 4121

### **DETAILED ACTION**

This is the first Office action in response to Application 10/771,412 filed on February 5, 2004. Claims 1-25 have been examined and are pending.

#### ***Priority***

1. Acknowledgment is made of applicant's claim for foreign priority based on an application filed in Japan on February 5, 2003.

#### ***Information Disclosure Statement***

2. The information disclosure statements (IDS) submitted on June 21, 2004, June 8 and July 27, 2007 were filed in compliance with the provisions of 37 CFR 1.97. Accordingly, the information disclosure statements have been considered by the examiner.

#### ***Specification***

3. The title of the invention is not descriptive. A new title is required that is clearly indicative of the invention to which the claims are directed.

#### ***Claim Objections***

4. Claim 11 objected to because of the following informalities: misspelling the word "first" in the line "...the *fst* access data is not transmitted...." Appropriate correction is required.

***Claim Rejections - 35 USC § 101***

5. 35 U.S.C. 101 reads as follows:

Whoever invents or discovers any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof, may obtain a patent therefor, subject to the conditions and requirements of this title.

6. Claims 22-25 are rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter.

Claims 22-24 recite "a computer program product" Claim 22, Claim Line 1. The computer program product is not limited to statutory subject matter. In view of Applicant's disclosure, specification page 10, paragraph [0154], the computer readable medium is not limited to tangible embodiments, instead being defined as including both tangible embodiments (e.g., "... data recording medium such as FD, memory card or CD-ROM...") and other possibly intangible embodiments (e.g., "...the invention need not be limited to such a configuration ..." ). As such, the claim is not limited to statutory subject matter and is therefore non-statutory.

Claim 25 is rejected in virtue of its being dependent on claim 24 which has been rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter.

Art Unit: 4121

***Claim Rejections - 35 USC § 102***

7. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

8. Claims 1-25 rejected under 35 U.S.C. 102(b) as being anticipated by US Patent Publication Number 2002/0156923 to Tanimoto.

Regarding claim 1, Tanimoto discloses **a communication system**

(Figure 1 and associated text; Tanimoto discloses a facsimile system, i.e. communication system.), **comprising: a communication device provided with an accessing system capable of accessing web pages** (Page 3, paragraph [0052]; Tanimoto discloses the facsimile machine, i.e. communication device, has an HTTP server means, i.e. accessing system, which can access data written in HTML (Hyper Text Markup Language) used for home pages, i.e. capable of accessing web pages.); **at least one operation member attachable to said communication device, said at least one operation member being operable with being attached to said communication system, said at least one operation member being**

**provided with a data storage containing first access data which is used by said communication device to access a first predetermined web page** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format based on indication message data by using the HTTP browser, i.e. a first predetermined web page.); **and a transmitting system that transmits the first access data contained in said data storage to said accessing system when said at least one operation member is operated while it is attached to said communication device, said accessing system accessing the first predetermined web page based on the first access data transmitted from said data storage of said at least one operation member** (Fig. 7-9 and associated text; Tanimoto discloses a facsimile server device which has a transmitting function and an accessing system described in steps S3-S6, S13-S15, and S20. The facsimile server device comprises storing means for storing image data obtained by receiving or obtained by scanning the original, image converting means for converting the stored image data into a

Art Unit: 4121

predetermined image data format based on indication message data obtained from each of the client.).

Regarding claim 2, Tanimoto discloses **the communication system according to claim 1, wherein said transmitting system is included in said at least one operation member, said transmitting system determines whether a predetermined condition is satisfied when said at least one operation member is operated with being attached to said communication system** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format, i.e. predetermined condition, based on indication message data, i.e. determining whether or not predetermined condition is satisfied.), **said transmitting system transmitting the first access data contained in said data storage to said accessing system when the predetermined condition is satisfied** (Fig. 7-9 and associated text; Tanimoto discloses a facsimile server device which has a transmitting function and an accessing system described in steps S3-S6, S13-S15, and S20. The facsimile server device comprises

Art Unit: 4121

storing means for storing image data obtained by receiving or obtained by scanning the original, image converting means for converting the stored image data into a predetermined image data format, i.e. predetermined condition, based on indication message data obtained from each of the client, i.e. based on whether or not predetermined condition has been satisfied.).

Regarding claim 3, Tanimoto discloses **the communication system according to claim 2, wherein said at least one operation member includes: a operation detection system that detects operation of said at least one operation member** (fig. 6-7; Tanimoto discloses a facsimile server device that has numerous operating components, i.e. operation members, such as a modem, display, recording unit, operation unit, ROM, CPU, and RAM. The device functions according to which function, i.e. operation, is performed.); **and a counting system that counts the number of times by which the first access data contained in said data storage is transmitted to said accessing system by said transmitting system, wherein said transmitting system determines that the predetermined condition is satisfied if the number of times counted by said counting system is less than a predetermined number when said operation detection system detects the operation of said at least one operation member, said transmitting system determining**



**the predetermined condition is not satisfied if the number of times counted by said counting system has reached the predetermined**

**number** (Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.).

Regarding claim 4, Tanimoto discloses **the communication system according to claim 3, wherein said communication device includes: a count inquiry system that transmits a count inquiry signal inquiring the number counted by said counting system to said at least one operation member** (Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display

Art Unit: 4121

indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.); **and a count notifying**

**system that notifies the number counted by said counting system based on a count response signal which is transmitted by said at least one operation member in response to the count inquiry signal transmitted thereto, and wherein said operation member includes: a count response system that output the count response signal to said communication device in response to the count inquiry signal transmitted from said communication device** (Fig. 15A and 15B;

Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated

Art Unit: 4121

what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.).

Regarding claim 5, Tanimoto discloses **the communication system according to claim 4, wherein said count inquiry system transmits the count inquiry signal when the first access data is transmitted from said at least one operation member** (Fig. 15A and 15B;

Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server

Art Unit: 4121

judges which actions to perform based on a predetermined condition that presents different cases or courses of action.).

Regarding claim 6, Tanimoto discloses **the communication system according to claim 4, wherein said communication device includes an attachment detection system that detects attachment of the operation member to said communication device** (fig. 6-7;

Tanimoto discloses a facsimile server device that has numerous operating components, i.e. operation members, such as a modem, display, recording unit, operation unit, ROM, CPU, and RAM. The device functions according to which function, i.e. operation, is performed.), **said count inquiry system outputting the count inquiry signal when said attachment detection system detects' attachment of said operation member** (Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par.

Art Unit: 4121

[0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.).

Regarding claim 7, Tanimoto discloses **the communication system according to claim 3, wherein said communication device includes: an allowed number inquiry system that transmits an allowed number inquiring signal inquiring the allowed number of times by which the readout of the first access data stored in the data storage is allowed to be read to said at least one operation member** (Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.); **and an allowed number notifying system that notifies the allowed**

Art Unit: 4121

**number based on a response signal which is transmitted by said at least one operation member in response to the allowance number inquiry signal transmitted thereto, and wherein said operation member includes: a response system that outputs the response signal to said communication device in response to the allowed number inquiry signal transmitted from said communication device**

(Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action. The user may enter the number of transmission or copies using the operation unit.).

Regarding claim 8, Tanimoto discloses **the communication system according to claim 7, wherein said allowed number inquiry system**

Art Unit: 4121

**transmits the allowed number inquiry signal when the first access data is transmitted from said at least one operation member** (Fig.

15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.).

Regarding claim 9, Tanimoto discloses **the communication system according to claim 7, wherein said communication device includes an attachment detection system that detects attachment of the operation member to said communication device** (fig. 6-7;

Tanimoto discloses a facsimile server device that has numerous operating components, i.e. operation members, such as a modem, display, recording unit, operation unit, ROM, CPU, and RAM. The

Art Unit: 4121

device functions according to which function, i.e. operation, is performed.), **said allowed number inquiry system outputting the allowed number inquiry signal when said attachment detection system detects attachment of said operation member** (Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.).

Regarding claim 10, Tanimoto discloses **the communication system according to claim 1, wherein said data storage contains second access data indicating a second web page as well as the first access data, and wherein said transmitting system transmits the second access data stored in said data storage to said accessing system if the predetermined condition is not satisfied when said operation**



Art Unit: 4121

**member is operated with being attached to said communication**

**device** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format based on indication message data by using the HTTP browser, i.e. a first predetermined web page. Fig. 8 and par. [0104-0105]; Tanimoto discloses the scanned image data is coded by the codec, and stored into the RAM (S2). The scanned image data is transmitted by a transmitting system to the G3 FAX or the mail client (S3). Then, the RAM stores the transmission management data, i.e. second access data, including the date and time of transmission, the number of pages of transmitted image data, the facsimile number, the data of the destination such as the mail address, and the transmission result received from the destination, regarding the transmitted image data (whether or not the image data has been delivered to the destination). This data is used to form an HTTP message as a URL, i.e. second web page.).

Regarding claim 11, Tanimoto discloses **the communication system according to claim 1, wherein said communication device includes: a device side detecting system that detects that said at least one operation member is operated with being attached to said communication device** (Fig. 6-7; Tanimoto discloses a facsimile server device, i.e. communication device, that has numerous operating components, i.e. operation members, such as a modem, display, recording unit, operation unit, ROM, CPU, and RAM. The device functions according to which function, i.e. operation, is performed.); **and a notification system that notifies that the first access data is not received since the predetermined condition is not satisfied if the first access data is not transmitted from said at least one operation member for a predetermined period** (Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a system that keeps track of transmissions in the transmitting system; see pg. 7, par.

Art Unit: 4121

[0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.).

Regarding claim 12, Tanimoto discloses **the communication system according to claim 1, wherein said transmitting system is included in said communication device, said transmitting system determines whether a predetermined condition is satisfied when said at least one operation member is operated with being attached to said communication system** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. communication device attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format, i.e. predetermined condition, based on indication message data, i.e. determining whether or not predetermined condition is satisfied.), **said transmitting system transmitting the first access data contained in said data storage to said accessing system when the predetermined condition is satisfied** (Fig. 7-9 and associated text; Tanimoto discloses a facsimile server device which has a transmitting function and an accessing system as described in steps S3-S6, S13-S15, and S20.

Art Unit: 4121

The facsimile server device comprises storing means for storing image data obtained by receiving or obtained by scanning the original, image converting means for converting the stored image data into a predetermined image data format, i.e. predetermined condition, based on indication message data obtained from each of the client, i.e. based on whether or not predetermined condition has been satisfied.).

Regarding claim 13, Tanimoto discloses **the communication system according to claim 12, wherein said data storage stores the readout number of times by which the first access data is transmitted by said transmitting system as well as the first access data** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image. Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission.), **wherein said communication device includes: a device side detection system that detects that said at least one**

Art Unit: 4121

**operation member is operated** (Fig. 6-7; Tanimoto discloses a facsimile server device that has numerous operating components, i.e. operation members, such as a modem, display, recording unit, operation unit, ROM, CPU, and RAM. The device functions according to which function, i.e. operation, is performed.); **a readout system that reads the readout number of times from said data storage when said device side detection system detects that said at least one operation member is operated** (Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.); **wherein said transmitting system determines that the predetermined condition is satisfied if the readout number has not**

Art Unit: 4121

**reached a predetermined number, said transmitting system determining that the predetermined condition is not satisfied when the readout number has reached the predetermined number** (Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.); **and wherein said communication device further includes a rewriting system that rewrites the readout number stored in said data storage of said at least one operation member with the readout number incremented by one when the first access data is read out by said transmitting system** (Fig. 9 and associated text; Tanimoto discloses a method for renewing, i.e. rewriting transmission management data is step S21. Fig. 15A

#### Art Unit: 4121

and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.).

**Regarding claim 14, Tanimoto discloses the communication system according to claim 13, wherein said communication device includes a notification system that notifies the readout number read out by said readout system** (Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was

Art Unit: 4121

performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.).

Regarding claim 15, Tanimoto discloses **the communication system according to claim 12, wherein said data storage contains an allowed number of times by which the first access data is allowed to be read out** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image. Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission.); **wherein said readout system reads out the readout number and the allowed number from said data storage when said device side detection system detects the**



Art Unit: 4121

**operation of said at least one operation member** (Fig. 15A and 15B;

Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.);

**wherein said transmitting system determines that the**

**predetermined condition is satisfied if the readout number has not**

**reached the allowed number** (Fig. 15A and 15B; Tanimoto discloses

views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how

Art Unit: 4121

many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.), **said transmitting system determining that the predetermined condition is not satisfied when the readout number has reached the allowed number** (Fig. 15A and 15B; Tanimoto discloses views showing an example of the display of the browser at the time of thread displaying of the saved image data. The display indicates the number of transmitted pages, the date and time of the transmission, the job order, and the destinations of the transmission. The display also indicated what operation was performed: retransmission, partial transmission, and records how many destinations were indicated. This indicates there is inherently a counting system that keeps track of transmissions in the transmitting system; see pg. 7, par. [0104]. Pg. 7, Par. [0108-0110]; The facsimile server judges which actions to perform based on a predetermined condition that presents different cases or courses of action.).

Regarding claim 16, Tanimoto discloses **the communication system according to claim 12, wherein said data storage contains second**

Art Unit: 4121

**access data indicating a second web page as well as the first access data, and wherein said transmitting system transmits the second access data stored in said data storage to said accessing system if the predetermined condition is not satisfied when said operation member is operated with being attached to said communication device** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile

server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format based on indication message data by using the HTTP browser, i.e. a first predetermined web page. Fig. 8 and par. [0104-0105]; Tanimoto discloses the scanned image data is coded by the codec, and stored into the RAM (S2). The scanned image data is transmitted by a transmitting system to the G3 FAX or the mail client (S3). Then, the RAM stores the transmission management data, i.e. second access data, including the date and time of transmission, the number of pages of transmitted image data, the facsimile number, the data of the destination such as the mail address, and the transmission result received from the destination, regarding the transmitted image data (whether or

Art Unit: 4121

not the image data has been delivered to the destination). This data is used to form an HTTP message as a URL, i.e. second web page.).

Regarding claim 17, Tanimoto discloses **a communication system** (Figure 1 and associated text; Tanimoto discloses a facsimile system, i.e. communication system.), **comprising: a communication device provided with an accessing system capable of accessing web pages** (Page 3, paragraph [0052]; Tanimoto discloses the facsimile machine, i.e. communication device, has an HTTP server means, i.e. accessing system, which can access data written in HTML (Hyper Text Markup Language) used for home pages, i.e. capable of accessing web pages.); **a plurality of operation members attachable to said communication device, each of said plurality of operation members being operable with being attached to said communication system, each of said plurality of operation members being provided with a data storage containing first access data which is used by said communication device to access a first predetermined web page** (Fig. 6-7; Tanimoto discloses a facsimile server device that has numerous operating components, i.e. operation members, such as a modem, display, recording unit, operation unit, ROM, CPU, and RAM. The device functions according to which function, i.e. operation, is performed. Pg.

Art Unit: 4121

3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format based on indication message data by using the HTTP browser, i.e. a first predetermined web page.); **an operation detection system that**

**identifies an operated one of said plurality of operation member**

(fig. 6-7; Tanimoto discloses a facsimile server device that has numerous operating components, i.e. operation members, such as a modem, display, recording unit, operation unit, ROM, CPU, and RAM. The device functions according to which function, i.e. operation, is performed.); **a transmitting system that transmits the**

**first access data contained in said data storage of said operated one of said plurality of operation member to said accessing system, said accessing system accessing the first predetermined web page based on the first access data transmitted by said transmitting system**

(Fig. 7-9 and associated text; Tanimoto discloses a facsimile server device which has a transmitting function and an accessing system described in steps S3-S6, S13-S15, and S20. The facsimile server device comprises storing means for storing image data

Art Unit: 4121

obtained by receiving or obtained by scanning the original, image converting means for converting the stored image data into a predetermined image data format based on indication message data obtained from each of the client.).

Regarding claim 18, Tanimoto discloses **an operation member for a communication system including a communication device capable of accessing web pages** (Fig. 6-7; Tanimoto discloses a facsimile system, i.e. communication system. Tanimoto further discloses a facsimile server device that has numerous operating components, i.e. operation members, such as a modem, display, recording unit, operation unit, ROM, CPU, and RAM. Page 3, paragraph [0052]; Tanimoto discloses the facsimile machine, i.e. communication device, has an HTTP server means, i.e. accessing system, which can access data written in HTML (Hyper Text Markup Language) used for home pages, i.e. capable of accessing web pages.), **said operation member being attachable to the communication device, said operation member being operable with being attached to the communication system, said operation member being provided with a data storage containing first access data which is used by the communication device to access a first predetermined web page** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to

Art Unit: 4121

facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format based on indication message data by using the HTTP browser, i.e. a first predetermined web page.), **when said operation member is operated with being attached to the communication device, the first access data contained in said data storage is transmitted to the communication device, which accesses the first predetermined web page based on the first access data transmitted from said data storage of said operation member** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format based on indication message data by using the HTTP browser, i.e. a first predetermined web page.).

Regarding claim 19, Tanimoto discloses **the operation member according to claim 18, wherein an indication related to the first web page being formed on a surface of said operation member** (Fig. 9

Art Unit: 4121

and associated text; Tanimoto discloses a facsimile transmission indication function described in step S19. The facsimile server device comprises storing means for storing image data obtained by receiving or obtained by scanning the original, image converting means for converting the stored image data into a predetermined image data format based on indication message data obtained from each of the client.).

Regarding claim 20, Tanimoto discloses **the operation member according to claim 18, comprising a transmitting system that transmits the first access data to the communication device** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format based on indication message data by using the HTTP browser), **said transmitting system determining whether a predetermined condition is satisfied when said operation member is operated with being attached to the communication system, said transmitting system transmitting the first access data contained in said data storage to the communication device when the predetermined condition is**



Art Unit: 4121

**satisfied** (Fig. 7-9 and associated text; Tanimoto discloses a facsimile server device which has a transmitting function and an accessing system attached to the facsimile system, i.e. communication system described in steps S3-S6, S13-S15, and S20. The facsimile server device comprises storing means for storing image data obtained by receiving or obtained by scanning the original, image converting means for converting the stored image data into a predetermined image data format, i.e. predetermined condition, based on indication message data obtained from each of the client, i.e. based on whether or not predetermined condition has been satisfied.).

Regarding claim 21, Tanimoto discloses **the operation member according to claim 18, wherein the communication device includes a transmitting system which determines whether a predetermined condition is satisfied when said operation member is operated with being attached to the communication system, the transmitting system transmitting the first access data contained in said data storage to the communication device when the predetermined condition is satisfied** (Fig. 7-9 and associated text; Tanimoto discloses a facsimile server device which has a transmitting function and an accessing system as described in steps S3-S6, S13-S15, and S20. The facsimile server device comprises storing

Art Unit: 4121

means for storing image data obtained by receiving or obtained by scanning the original, image converting means for converting the stored image data into a predetermined image data format, i.e. predetermined condition, based on indication message data obtained from each of the client, i.e. based on whether or not predetermined condition has been satisfied.).

Regarding claim 22, Tanimoto discloses **a computer program product defining a procedure to be executed by a computer employed in a communication system** (Pg. 3, par. [0061-0062]; Tanimoto discloses an application program, i.e. computer program, stored on a storing medium that performs functions in the facsimile system. This is a computer program product.), **the communication system including a communication device provided with an accessing system capable of accessing web pages** (Page 3, paragraph [0052]; Tanimoto discloses the facsimile machine, i.e. communication device, has an HTTP server means, i.e. accessing system, which can access data written in HTML (Hyper Text Markup Language) used for home pages, i.e. capable of accessing web pages.), **at least one operation member attachable to the communication device, the at least one operation member being operable with being attached to the communication system, the at least one operation member being provided with a data storage**

**containing first access data which is used by the communication device to access a first predetermined web page** (Pg. 3, par.

[0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format based on indication message data by using the HTTP browser, i.e. a first predetermined web page.), **and a transmitting system that transmits the first access data contained in the data storage to the accessing system when the at least one operation member is operated while it is attached to the communication device, the accessing system accessing the first predetermined web page based on the first access data transmitted from the data storage of the at least one operation member, the computer that executes the procedure defined by the computer program product functioning as the communication device** (Fig. 7-9 and associated text; Tanimoto discloses a facsimile server device which has a transmitting function and an accessing system described in steps S3-S6, S13-S15, and S20. The facsimile server device comprises storing means for storing image data obtained by receiving or obtained

Art Unit: 4121

by scanning the original, image converting means for converting the stored image data into a predetermined image data format based on indication message data obtained from each of the client.).

Regarding claim 23, Tanimoto discloses **the computer program product according to claim 22** (Pg. 3, par. [0061-0062]; Tanimoto discloses an application program, i.e. computer program, stored on a storing medium that performs functions in the facsimile system. This is a computer program product.), **wherein the transmitting system is included in the communication device, the computer that executes the procedure defined by the computer program product functioning as the transmitting system** (Pg. 3, par. [0061-0062]; Tanimoto discloses an application program, i.e. computer program that is executed by the main control unit, i.e. computer employed in the facsimile system.), **the transmitting system determining whether a predetermined condition is satisfied when the at least one operation member is operated with being attached to the communication system** (Pg. 3, par. [0053]; Tanimoto discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first

Art Unit: 4121

access data, image converting means for converting the stored image data into a predetermined image data format, i.e. predetermined condition, based on indication message data, i.e. determining whether or not predetermined condition is satisfied.), **the transmitting system transmitting the first access data contained in the data storage to the accessing system when the predetermined condition is satisfied** (Fig. 7-9 and associated text; Tanimoto discloses a facsimile server device which has a transmitting function and an accessing system as described in steps S3-S6, S13-S15, and S20. The facsimile server device comprises storing means for storing image data obtained by receiving or obtained by scanning the original, image converting means for converting the stored image data into a predetermined image data format, i.e. predetermined condition, based on indication message data obtained from each of the client, i.e. based on whether or not predetermined condition has been satisfied.).

Regarding claim 24, Tanimoto discloses **a computer program product defining a procedure to be executed by a computer employed in a communication system** (Pg. 3, par. [0061-0062]; Tanimoto discloses an application program, i.e. computer program, stored on a storing medium that is executed by the main

Art Unit: 4121

control unit, i.e. computer employed in the facsimile system.

This is a computer program product.), **the communication system including a communication device provided with an accessing system capable of accessing web pages** (Page 3, paragraph [0052];

Tanimoto discloses the facsimile machine, i.e. communication device, has an HTTP server means, i.e. accessing system, which can access data written in HTML (Hyper Text Markup Language) used for home pages, i.e. capable of accessing web pages.), **at**

**least one operation member attachable to the communication device, the at least one operation member being operable with being attached to the communication system, the at least one operation member being provided with a data storage containing first access data which is used by the communication device to access a first predetermined web page** (Pg. 3, par. [0053]; Tanimoto discloses

the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format based on indication message data by using the HTTP browser, i.e. a first predetermined web page.),

**and a transmitting system that transmits the first access data**

Art Unit: 4121

**contained in the data storage to the accessing system when the at least one operation member is operated while it is attached to the communication device, the accessing system accessing the first predetermined web page based on the first access data transmitted from the data storage of the at least one operation member** (Fig. 7-9 and associated text; Tanimoto discloses a facsimile server device which has a transmitting function and an accessing system described in steps S3-S6, S13-S15, and S20. The facsimile server device comprises storing means for storing image data obtained by receiving or obtained by scanning the original, image converting means for converting the stored image data into a predetermined image data format based on indication message data obtained from each of the client.), **the computer that executes the procedure defined by the computer program product functioning as the transmitting system** (Pg. 3, par. [0061-0062]; Tanimoto discloses an application program, i.e. computer program that is executed by the main control unit, i.e. computer employed in the facsimile system.).

Regarding claim 25, Tanimoto discloses **the communication system according to claim 24, wherein the transmitting system is included in the at least one operation member, the transmitting system determining whether a predetermined condition is satisfied when**

Art Unit: 4121

**the at least one operation member is operated with being attached to the communication system** (Pg. 3, par. [0053]; Tanimoto

discloses the facsimile server device, i.e. operation member attached to facsimile machine as part of facsimile system, comprises storing means for storing image data obtained by receiving or obtained by scanning the original, i.e. first access data, image converting means for converting the stored image data into a predetermined image data format, i.e. predetermined condition, based on indication message data, i.e. determining whether or not predetermined condition is satisfied.), **the transmitting system transmitting the first access**

**data contained in the data storage to the accessing system when the predetermined condition is satisfied** (Fig. 7-9 and associated text;

Tanimoto discloses a facsimile server device which has a transmitting function and an accessing system as described in steps S3-S6, S13-S15, and S20. The facsimile server device comprises storing means for storing image data obtained by receiving or obtained by scanning the original, image converting means for converting the stored image data into a predetermined image data format, i.e. predetermined condition, based on indication message data obtained from each of the client, i.e.



Art Unit: 4121

based on whether or not predetermined condition has been satisfied.).

### ***Conclusion***

9. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure:

- US Patent Number 5,901,286 to Danknick et al titled, "Method and Apparatus for Communicating with a Network Peripheral."
- US Patent Number 6,012,083 to Savitzky et al titled, "Method and Apparatus for Document Processing Using Agents to Process Transactions Created Based on Document Content."
- US Patent Number 6,230,189 to Sato et al titled, "Apparatus and Method for an HTTP Server Capable of Connecting Facsimile Apparatuses and Data Terminals."
- US Patent Number 6,289,371 to Kumpf et al titled, "Network Scan Server Support Method Using a Web Browser."
- US Patent Number 6,134,017 to Schlank et al titled, "Facsimile Manager."
- US Patent Number 6,396,848 to Ohta titled, "Apparatus and Method of Allowing User to Browse History of Relay Transmission on Data Terminal."
- US Patent Number 6,003,087 to Housel et al titled, "CGI Response Differencing Communication System."

Art Unit: 4121

- US Patent Number 6,363,421 to Barker et al titled, "Method for Computer Internet Remote Management of a Telecommunication Network Element."
- US Patent Number 6,850,986 to Peacock titled, "Method and System for Implementing URL Scheme Proxies on a Computer System."
- US Patent Number 6,976,084 to Pineau et al titled, "Method and Apparatus for Printing Remote Images Using a Network-Enabled Printer."
- US Patent Number 7,024,475 to Abaye et al titled, "Performance Modeling of a Communications System."
- US Publication Number 2003/0014533 to Greene et al titled, "Method and Apparatus for Facilitating Attention to a Communication."
- US Publication Number 2003/0182438 to Tenenbaum titled, "Methods and Systems for the Provision of Printing Services."
- US Publication Number 2004/0068576 to Lindbo et al titled, "Internet Communication System."

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Tariq S. Najee-ullah whose telephone number is (571) 270-5013. The examiner can normally be reached on Monday through Friday 8:00 - 5:30 EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Taghi T. Arani can be reached on (571) 272-3787.

Art Unit: 4121

The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

TN  
/Taghi T. Arani/  
Supervisory Patent Examiner, Art Unit 4121  
12/06/2007